GALCON 6100 SERIES PROGRAMMER

6100 bank-powered irrigation programmer, designed to automate irrigation systems without the need for electrical connection, independent programming of each valve and general valve, and sequential irrigation mode.







MATERIAL CHARACTERISTICS

Body: ABS Plastic

Cover: ABS Plastic

Screen: LCD (Liquid Crystal Display) - Liquid Crystal

OPERATING CHARACTERISTICS

Power: 2 9V alkaline bank.

Control capacity: , 4, 6 and 12 stations, depending on model.

Pressure range: 0,5 to 10 bar.

Working temperature: 5 °C to 50 °C.

Direct connection to 9V latch solenoid valves.

IP68 protection.

MODELS

CODE	OUTPUT	CONNECTION	VOLTAGE	UNITS/BOX	RRP (€)
11033004	4	3 THREADS	9V LATCH	1	**154**
11033007	6	3 THREADS	9V LATCH	1	**192.5**
11033018	4	2 THREADS	9V LATCH	1	**154**
11033019	6	2 THREADS	9V LATCH	1	**192.5**
11033015	12	3 THREADS	9V LATCH	1	**627**
11033016	12	2 THREADS	9V LATCH	1	**656**
11033002	PROGRAMMER + VALVE 1"	3 THREADS	9V LATCH	1	**198**
11033001	PROGRAMMER + 1 SOLENOID	3 THREADS	9V LATCH	1	**171.6**

ACCESSORIES



LONG DISTANCE SOLENOID

SEE PAGE



SOLENOID 2 ways		
CODE	CONNECTION	RRP (€)
	LATCH 2HILOS	**26**
	24VAC	**24**



SOLENOID galcon e vias		
CODE	MODEL	RRP (€)
11021041	2H LATCH	**77**
40001221	3H LATCH	**77**