G75 PROGRAMMER

The G75 programmer allows you to automate irrigation cycles in a simple and reliable way. It works with 9 V bank and is installed directly on the valve or on the wall. Its compact, resistant and completely waterproof design makes it ideal for outdoor use or agricultural environments.







MATERIAL CHARACTERISTICS

Housing: ABS technical plastic

Front panel: Transparent polycarbonate with UV protection

Button pad: Membrane-type sealed rubber.

Screen: Low consumption LCD

OPERATING CHARACTERISTICS

Power: 9 V bank (autonomy > 1 year)

Programming: Up to 3 daily starts and irrigation day selection

Mounting: Direct on valve or on wall using support

Working temperature: –10°C to +60°C

Protection grade: IP67

MODELS

CODE	OUTPUT	MODEL	VOLTAGE	UNITS/BOX	RRP (€)
11030002	1	PROGRAMMER + SOLENOID	9V LATCH	1	**98**
11030001	1	PROGRAMMER + VALVE 1"	9V LATCH	1	**106**

RELATED ARTICLES



LONG DISTANCE SOLENOID

SEE PAGE



SOLENOID 2 ways

CODE	CONNECTION	RRP (€)
	LATCH 2HILOS	**26**
	24VAC	**24**



PROCELL 9V BATTERIES

CODE	MODEL	RRP (€)
11033013	9V ILR	**4.2**