ACOPLE RÁPIDO CAMLOCK

CAMLOCK quick coupler designed to facilitate the connection and disconnection of hoses in irrigation tanks and spray systems. Made of polypropylene reinforced with fiberglass, it offers high mechanical and chemical resistance.







MATERIAL CHARACTERISTICS

Body: Polypropylene reinforced with fiberglass.

Locking levers: Stainless steel.

Thread: BSP female thread.

OPERATING CHARACTERISTICS

Maximum working pressure: 10 bar.

Working temperature: -10°C to **+60°C.**

Locking system: Stainless steel levers to prevent accidental disconnections.

Connections: Available from ¾" to 4".

MODELS





MALE THREAD QUICK COUPLING		
CODE	MODEL	RRP (€)
13076015	1-1/2"	30
13076016	2"	37

FEMALE THREAD QUICK COUPLING		
CODE	MODEL	RRP (€)
13076017	1-1/2"	30
13076018	2"	37

MODELS



MALE THREAD ADAPTER		
CODE	MODEL	RRP (€)
13076028	1-1/2”	10
13076029	2”	13



FEMALE THREAD ADAPTER		
CODE	MODEL	RRP (€)
13076021	1-1/2”	10
13076022	2”	13



SPIN ADAPTER		
CODE	MODEL	RRP (€)
13076019	50	10
13076020	63	13



PVC WALL GALLS		
CODE	MODEL	RRP (€)
13076004	3/4”	21
13076005	1”	27
13076006	1-1/4”	28
13076007	1-1/2”	32
13076008	2”	45