Our Iflowcontrol microirrigation accessories are the definitive solution for Agriculture, Gardening and Landscaping, offering a secure fit thanks to their serrated connection design, they are completely resistant to UV rays.



MATERIAL CHARACTERISTICS

Body: POM (Polyamide).

OPERATING CHARACTERISTICS

16 diameter mm.

For drip pipes with inner diameters of 14.2mm and 15.2mm.

Maximum recommended pressure 3.45 bar.

MODELS



CODE	CONNECTION (MM)	PRODUCT	CAJAS (UDS)	RRP (€)
15156001	16	LINK	1800	**0,08**



CODE	CONEXIÓN	PRODUCTO	CAJAS (UDS)	RRP (€)
15156007	16	CTR	2400	**0,09**

MODELS



CODE	CONNECTION (MM)	PRODUCT	CAJAS (UDS)	RRP (€)
15156009	16	CTR JOINT	1200	**0,11**



CODE	CONNECTION (MM)	PRODUCT	CAJAS (UDS)	RRP (€)
15156008	16	CRUZ	500	**0,29**



CODE	CONNECTION (MM)	PRODUCT	CAJAS (UDS)	RRP (€)
15156002	16	TE	800	**0,19**



CODE	CONNECTION (MM)	PRODUCT	CAJAS (UDS)	RRP (€)
15156020	16	PEAK	1000	**0,21**



CODE	CONNECTION (MM)	PRODUCT	CAJAS (UDS)	RRP (€)
15156003	16	ELBOW 90º	1000	**0,17**



CODE	CONNECTION (MM)	PRODUCT	CAJAS (UDS)	RRP (€)
15156024	16	VALVE	700	**0,6**